



PM 480

Reciprocating Horizontal
Quintuplex Plunger Pumps



PM 480



General features

- Compact dimension
- Low noise
- Forced lubrication system
- Easy maintenance
- Low maintenance costs
- Internal double reduction gear with helical gears
- Input shaft can be placed on either side of the pump
- Self-adjusting seal packing
- Available with carbon steel or stainless steel hydraulic head
- Low vibrations
- Constant hydraulic flow with minimal pulsation: no pulsation dampener required
- 100% aluminium free


Accessories

- Valve lifter controlled by means of pneumatic solenoid
- Unloading valve
- Over-pressure valve
- HP check valve
- Suction and/or delivery gauge
- Low and high pressure switches
- Manifold groups for suction/delivery
- ATEX Group I Category M2 Certification

Applications

- Emulsion Hydraulic power to drive
- Longwall systems
- Dust suppression systems on Roof
- Supports & Coal Shearers

Pulsation diagram




Identification code

see tables on the next page > > >

PM						
SIZE	SHAPE	Ø PLUNGER	HYDRAULIC HEAD MATERIAL	LUBRICATION	ATEX	
480	STD	50	S Carbon steel	4 Forced + water/air heat exchanger (at customer care)	Ex	Atex pump
481	SX	55	Ø Stainless steel			
482	DUAL	60				
		65				
		70				
	RATIO		HYDRAULIC HEAD VERSION			
	L		Q48 NP 420 bar max.			
	M		Q49 NP 420 bar max. + Valve lifter			
	V					


Dimensions

Dimensions are referred to hydraulic head Q48
Weight: kg 1670




Selection Diagram

PM 480 - 50 Hz 4 POLES ELECTRIC MOTOR (1500 RPM) - MAX ABSORBED POWER 400 kW



PM 480 - 60 Hz 4 POLES ELECTRIC MOTOR (1800 RPM) - MAX ABSORBED POWER 400 kW



Also covered by smaller pump models

Q48/Q49 Hydraulic head

1 MPa = 10 bar. The pump performances are referred to a volumetric efficiency of 100% and a mechanical efficiency of 89%, with water at 20°C. Input speed range 900-1800 r.p.m. For performances and uses other than the ones listed in this catalogue, please contact INOXIHP technical office for assistance.

Mining Skid

Inoxihp supplies complete skids for underground coal mining (Longwall) for applications such as tunnel roof support, rotating blade cooling (shearer) and dust suppression.

Highly reliable products, also available in ATEX version.



INOXIHP S.r.l.

IT - 20834 Nova Milanese (MB) - Via Garibaldi, 89 - Tel: +39 0362 190111
Fax: +39 0362 1901008 - E-mail: inoxihp@inoxihp.com - inoxihp.com

INOXIHP
ABOUT USING WATER