


INOX IHP
ABOUT USING WATER



VPZ-R

Pressure Regulating Valve
Air Actuated



VPZ-R

General features

- Very smooth valve response (no shocking impact)
- Metal-to-metal seal
- Easy maintenance
- Pneumatic control valve

Options

- Proportional pressure regulation air solenoid valve kit
- Flanges kit
- Body in stainless steel
- Drilling for ANSI and special flanges
- FRL group

Applications


- Designed to be used as pressure relief valves

Technical data





Fluid:	Water and HFA
Working pressure:	D= 6 ÷ 15 MPa, F= 15 ÷ 30 MPa, G= 30 ÷ 50 MPa
Ambient temperature:	+2°C ÷ +60°C
Feeding:	Lubricated compressed air 0,5 ÷ 0,7 MPa
Electrical input:	0 ÷ 10 V
Connections:	SAE6000 drilling up to 30 MPa, INOXIHP drilling 50 MPa
Materials:	Body in carbon steel and internal parts in stainless steel

Panel version

Line version



Selection diagram



Valves sizes

INOXIHP	ND	inches
02	10	3/8"
03	15	1/2"
05	25	1"
07	40	1 1/2"

EAC This valve model is EAC certified



INOXIHP S.r.l.
 IT - 20834 Nova Milanese (MB) - Via Garibaldi, 89 - Tel: +39 0362 190111
 Fax: +39 0362 1901008 - E-mail: inoxihp@inoxihp.com - inoxihp.com

INOXIHP
 ABOUT USING WATER